

-32-

CLAIMS

1. A display apparatus, comprising:
 - a display device comprising a plurality of
 - 5 pixels arranged in a matrix,
 - a drive circuit for outputting a gradation
 - signal to each of the pixels, and
 - a correction circuit for correcting the
 - gradation signal at each pixel so that a desired
 - 10 gradation can be provided by compensating an influence
 - from adjacent pixels.
2. An apparatus according to Claim 1, wherein
 - the plurality of pixels include a correction pixel at
 - 15 which a gradation signal is corrected by said
 - correction circuit and adjacent pixels surrounding the
 - correction pixel, and said correction circuit obtains
 - a gradation signal, to be corrected, on the basis of
 - information on a gradation to be provided at the
 - 20 correction pixel and information on a gradation to be
 - provided at the adjacent pixels.
3. An apparatus according to Claim 2, wherein
 - said apparatus further comprises a first storing
 - 25 device which stores a relationship between states of
 - the adjacent pixels, a gradation to be provided at the
 - correction pixel, and a gradation signal to be applied

-33-

to the correction pixel so as to provide a desired gradation at the correction pixel, said correction circuit obtaining the gradation signal to be applied to the correction pixel on the basis of data stored in
5 the first storing device.

4. An apparatus according to Claim 1, wherein the correction of the gradation signal by the correction circuit is effected when a deviation ratio
10 of a display gradation is out of a predetermined range.

5. An apparatus according to Claim 1, wherein the display device is an electrophoretic display
15 device for displaying various information by moving charged electrophoretic particles or a liquid crystal display device for displaying various information by applying a voltage to a liquid crystal.

20

25